



*Dove* **MKIII** TRAVELS FREE AS A BIRD





## POWER UNIT

**DOVE MK III** You'll feel free as a bird as it wings away smoothly and quietly with its automatic take-off gear.

The engine develops 2 h.p. at 5,600 r.p.m. It will cruise comfortably and willingly soaring above hills and dales in effortless wonder.

## REAR SUSPENSION

**DOVE MK III** travels free as a bird, with swinging arm rear suspension and hydraulic shock absorbers to smooth out the bumpy roads and make you feel you are flying rather than driving.



## FRONT SUSPENSION

Front Suspension with robust telescopic type front forks gives you smooth steering and positive cornering. For added safety and smooth travel soar away on a **DOVE MK III**. Note the powerful full width hub brakes.





## **DEEM** TRAVEL FREE AS A BIRD

# *Dove* **MKIII**

Full width hub-type brakes makes stopping as easy as starting and you will find your way easily in the dark with the 18 watt headlamp unit. You'll certainly feel free when you drive away. The walk-through frame makes it easy to ride — there is absolutely nothing to learn — it's all automatic when you ride a DOVE MK III. The fuel consumption will surprise you for it goes on and on and will travel over 180 miles to one gallon of petrol/oil. Go into your nearest Dealer Showroom now and join the DOVE MK III travellers - feel free as a bird.



## SPECIFICATION OF MAIN FEATURES OF THE DEMM «DOVE MK III»

### MAIN FEATURES

Overall length: 64"  
width: 28"  
height: 38"  
Saddle height: 31"  
Wheel Base: 42"  
Main Frame (pressed steel construction)  
Front suspension: Telescopic type forks  
Rear suspension: Swinging arm with spring/hydraulic shock absorbers  
Centre stand  
Fuel Tank Capacity:  $\frac{3}{4}$  Gallon (5 pints Main - 1 pint Reserve)  
Fuel Consumption: 180 miles per gallon (approximately)

### CARBURETTOR

Dell'Orto: SHA 14/12

### TRANSMISSION

Chain from engine sprocket to rear wheel  
Rear Sprocket: 34 teeth  
Engine Sprocket: 11 teeth

### ENGINE

Single cylinder two-stroke air cooled  
Bore: 38.80 mm  
Stroke: 42 mm  
Capacity: 49.65 cc  
Compression Ratio: 8.5 : 1  
Maximum Output: @ 5600 RPM - 2 HP  
6 volt AC lighting system  
Ignition by 18 watt alternator flywheel magneto  
Spark Plug Type: CHAMPION L7  
Lubrication: Petrol/oil mixture  
Oil bath gear case lubrication  
Automatic centrifugal clutch in oil bath

### WHEELS AND BRAKES

Wheel size: 16"  
Tyre size - front:  $2\frac{1}{4}$  x 16  
rear:  $2\frac{1}{4}$  x 16  
Full width hub brakes.

## MOTORISED CYCLES LTD

87 Beddington Lane-Croydon CR04TD Surrey England Tel. 01-689-3471 Telex 21138 Cables: Suzuki Croydon



OFFICINE MECCANICHE F.LLI DALDI & MATTEUCCI S.p.A.  
20124 MILANO (ITALY) - Via Pirelli, 16 A - Phone (02)653.651 (5 lines)  
Telex 32276 DEMM-MI - Cable: INGRADALDI - MILANO

# IceniCAM Information Service

