











### SOME ADVANTAGE OF «ISSIMO»

· Remarkable space which enables the legs to pass through easily while getting on and out of the moped and a wide, very comfortable footboard, which allows the sports drive.

· Telescopic suspension of the front wheel. Very strong oil bath fork with long stroke.

2.50 x 16" large section tyres which combine a better elasticity with

a greater roadability and a longer life.

· Two-stroke engine with automatic transmission in oil bath. Aluminium enlarged cylinder head with centrifugal fan which assures an excellent cooling and a constant power output even in very bad conditions.

· Overhead, super comfort two-seater saddle to have acces to the

Very light, easy to be replaced plastic mudguards, can undergo blows without any buckling.

Extended exhaust system which assures a remarkable ride noiseles-

Telescopic shock absorbers which offer an excellent roadability and the maximum ride comfort.

· The new type of watertight pivotable headlight and dashboard where the speedometer can be inserted, antitheft padlock in special steel. The fuel tank line assures the best protection (legs-guard screen) and built-in case.

#### TECHNICAL SPECIFICATIONS

ENGINE: 2 stroke, single cylinder, forced air-cooling.

BORE AND STROKE: 38,8 x 42 m/m.

DISPLACEMENT: 49.6 cc.

COMPRESSION RATIO: 8.6 to 1.

CARBURETTOR: Dell'Orto SHA 14/12 with semiautomatic choke.

LUBRICATION SYSTEM: gasoline with 2% oil (ratio 50 : 1)

IGNITION AND LIGHTING: by flywheel magneto 6V 18W with internal coil.

STARTING: kickstarter or pedals.

TRANSMISSION: centrifugal automatic clutch and primary transmission by helicoidal gears running-in oil. Secondary transmission by roller chain - 1/2 x 3/16".

FRAME: super strong tubular steel.

MUDGUARDS: plastic unbreakable material

SUSPENSIONS: front telescopic fork, rear swing arm with telescopic shocks.

WHEELS: steel or aluminium rims front and rear WMO/1.5 x 16" with front and rear brake drum Ø 90 m/m.

TIRES: front and rear 2.1/2 x 16"

STANDARD EQUIPMENT: illuminated speedometer, steering lock, one rear view mir-


FUEL TANK: steel plate, capacity approx. It. 3,2 including reserve, 3 positions gas tap.


FUEL RATE: lt. 2.5/100 Km DRY WEIGHT: Kg. 47.

MAX SPEED: conform the moped legislation.













## **OPTIONAL ACCESSORIES**

3

- 1. Pair of waterproof cloth bags dis. 311.15.5090.
- 2. Pair of bags in ABS complete of bag supports and screw dis. 310.15.5080
- 3. Rear plasticized basket assembly dis. 310.15.5060
- 4. Weathershield with fittings dis. 310.15.5200
- 5. Rear mirror dis. 322.15.5180
- 6. Lighted speedometer assembly dis. 310.16.6600 (C.E.V.) dis. 311.16.6600 (BORLETTI)
- 7. Complete overhead double seat dis. 311.06.5000



PRINTED IN ITALY - 7/79 - DIS. 187.93.5150

# FANTIC MOIOR

# IceniCAM Information Service

