
HONDA PCSO





Technical Specification

Engine Unit

Type: Air Cooled, Single Cylinder, 4 Stroke O.H.V. Cylinder

inclined 10° from horizontal.

Bore & Stroke: 42 mm × 35.6 mm (1.6535 ins × 1.4016 ins)

Cylinder Capacity: 49 cc (3·0 cu ins) Compression Ratio: 8·5–1

Carburettor: Keihin. Piston Valve Type

Ignition: Flywheel Magneto

Lighting: Direct. Headlamp 6 Volt 18/18W

Lubrication System: Wet Sump Oil Capacity: 0.75 litre (1.33 pts) Starting Method: By Pedals Spark Plug: N.G.K. Type C7HS Clutch: Automatic Centrifugal Type

Transmission: Single Speed, Chain Drive to Rear Wheel

Primary Reduction: 3.000 Internal Reduction: 3.214 Secondary Reduction: 1.933 Overall Gear Ratio: 18.63-1

Maximum Power: 1.80 P.S. @ 5,700 R.P.M.

Maximum Torque: 0·29 Kg-m @ 3,500 R.P.M. (2·1 lbs ft) Engine Weight: (Inc. Oil) 12 Kg (26·45 lbs)

Type: Pressed Steel. Open Frame Type

Front Suspension: Leading Link Type Pressed Steel Fork

Rear Suspension: Swinging Arm Tyres: Front 2.00 × 19 2 Ply Rear 2.25 × 19 2 Ply

Tyre Pressures: Front 2·0 Kg—cm² (28·5 p.s.i.) Rear 2·0 Kg—cm² (28·5 p.s.i.)

Brakes: Front. Internal Expanding Type. Cable Operated

Rear. Internal Expanding Type. Cable Operated

Petrol Tank Capacity: 3 litres (0.66 gallons) Overall Length: 1755 mm (69·10 ins) Overall Width: 600 mm (23.62 ins) Overall Height: 1035 mm (40.75 ins) 1130 mm (44·50 ins) Wheelbase: 780 mm (30.71 ins) Seat Height: Ground Clearance: 140 mm (5.52 ins) Curb Weight: 50 Kg (110-23 lbs)

Standard Equipment


Driving Mirror, Speedometer, Steering Lock, Electric Hooter, and Tool Kit.

Honda (UK) Ltd Power Road Chiswick London W4 Telephone 01-995 9381

These specification details do not apply to any particular product which is supplied or offered for sale. The manufacturers reserve the right to vary their specification with or without notice and at such times and in such manner as they think fit. Major as well as minor changes may be involved. Every effort, however, is made to ensure the accuracy of the particulars contained in this brochure. Consult the Dealer with whom your order is

placed for details of the specification of any particular product. This publication shall not constitute in any circumstances whatsoever an offer by the Company to any person. All sales are made by the Distributor or Dealer concerned subject to and with the benefit of the standard Conditions of Sale and Warranty given by the Distributor or Dealer, copies of which may be obtained from him on request."

IceniCAM Information Service



www.icenicam.org.uk