
IceniCAM Information Service



www.icenicam.org.uk

Estabe 1870

DISTINCTIVE IN DESIGN



DEPENDABLE IN SERVICE



CYCLES

MO. L. JULYAN


SEE THE BICYCLE



THE GOLDEN RING

CITY OS ETSAS SERVEY ELLL

Head Office & Works: BIRMIN GHAM tondon Showrooms: 21322 HOLBORN VIADUCTES



"THE BICYCLE WITH THE GOLDEN RING"

- 1 THE JAMES ROYAL TWO-SPEED BICYCLE No. 21

THE JAMES ROYAL TWO-SPEED

Patent No. 3967/28.

"THE BICYCLE WITH THE GOLDEN RING"

is fitted with a "James" Patent Two-speed gear which fulfils every demand made by the rider on any kind of road.

The normal or top gear enables the rider to travel at a rapid speed on the level, while the second or power gear provides all that is necessary to make climbing any ordinary hill an easy task, and with the use of the free wheel for down hill the triple combination gives all the comfort and ease that the most exacting cyclist can

The "James" Patent Two-speed Gear is far superior to a complicated three-speed gear, because :-

- (1) It is simplicity itself and cannot get out of order.
- (2) It is much easier for the rider to operate.
- (3) It renders a third gear unnecessary.
- (4) It has in actual practice efficient than a complicated three-speed gear.
- The weight is in the correct place, and does not interfere with the "liveliness" of the bicycle.
- (6) It is not an experiment.
- It is thoroughly well made and practically everlasting.

The "James" Two-speed Gear is the James Cycle Co.'s own Patent, and is fully guaranteed by them. It is only fitted to "James" Bicycles, and is manufactured throughout in their own works.

Its popularity is proved by the thousands already sold.

You have only to ride a famous "James," the bicycle with the Golden Ring, to realise the real pleasure of Cycling.

SPECIFICATION

LADY'S MODEL

FRAME WHEELS HUBS .. TYRES BRAKES SADDLE CHAIN TWO-SPEED GEAR

"THE BICYCLE WITH THE GOLDEN RING"

THE JAMES ROYAL TWO-SPEED BICYCLE No. 20

Low-built of best Weldless High Carbon Steel Tube, 22 in., and 24 in. sizes.

26 × 1½ in., Enamelled Black, Lined Red. James Patent Stud, Straight Pull Spokes. Dunlop Full Roadster.

James Front and Rear Rim, with Brazed Fittings throughout, simple and efficient adjustment. Brooks' B75, Three-coil, Enamelled Springs. Hans Renold, ½ ½ in. James (Patent No. 3967/28) Improved Two-speed, giving reduction of 25 per cent, from normal to power gear, Standard Gears 64, and 47. formal to power gear, Standard Gears 64 and 47. James Registered Oil-bath, detachable from

PEDALS MUDGUARDS FREE WHEEL HANDLEBAR

GEARCASE ..

FINISH

EQUIPMENT

frame.
Divided Rubber.
Divided Rubber.
Deep and Wide Car Section, with Deep Valance
to Front and Rear.
James Best Quality, Full Ball-Bearing.
As illustrated, covered with Celluloid to Brazed
Brake lugs. Brake lugs.

All-Back Enamel on Rust-proofed surface,
Lined Fine Red.
Toolbag, necessary Spanners, Offer, Celluloid
Inflater, approved Rear Reflector.

£8:0:0 net cash

Easy Payment Terms - 12 Payments of 16/- each.



The illustration shows the "James" Patent Bracket Two-speed Gear taken apart to show the extreme simplicity of the mechanism. There is nothing fragile and liable to go wrong or break included in its design. On the normal or top gear, the gear revolves solid on the usual bracket axle bearings, no extra mechanism being in use. On the low or power gear, all parts are running on ball bearings, as illustrated above.

DISTINCTIVE IN DESIGN

Head Office and Works

SPECIFICATION

GENT'S MODEL

FRAME WHEELS HUBS .. TYRES BRAKES

Low-built of best Wedless High Carbon Steel Tube, 22 in., 24 in., and 26 in. slzes; 28 × 1½ in., Enamelled Black, Lined Red. James Patent Stud, Straight Pull Spokes. Dunlop Full Roadster.

James Front and Rear Rim, with Brazed Fittings throughout, simple and efficient adjustment. Brooks' B75, Three-coil, Enamelled Springs. Hans Renold, ½ × ½ in. James (Patent No. 3967/28) Improved Two-speed, giving reduction of 25 per cent. from normal to power gear. Standard Gears 72 and 54.

James Registered Off-bath, detachable from frame.

CHAIN TWO-SPEED GEAR GEARCASE ...

SADDLE

frame.
Divided Rubber.
Divided Rubber.
Deep and Wide Car Section, with Deep Valance
to Front and Rear.
James Best Quality, Full Ball-Bearing.
As illustrated, covered with Celluloid to Brazed
Dee Values. PEDALS ...

Brake lugs.


All-Black Enamel on Rust-proofed surface,
Lined Fine Red.
Toolbag, necessary Spanners, Oiler, Celluloid
Indiater, approved Rear Reflector. FINISH EQUIPMENT

£7:15:0 net cash

Easy Payment Terms - 12 Payments of 15/6 each.

The "James" Improved Bracket Two-speed Gear (Patent No. 3967 28).

"The greatest advance made in recent years for the benefit of cyclists."



The Gear that takes the "Push" out of Cycling.

DEPENDABLE IN

THE JAMES CYCLE COMPANY, LTD.

GREET, BIRMINGHAM

THE JAMES ROYAL TWO-SPEED

Patent No. 3957/28.

"THE BICYCLE WITH THE GOLDEN RING"



View showing the "James" Patent Bracket Two-speed Gear assembled on bracket axle, showing that no extra width of tread is involved: the top illustration shows the control lever—as easy to use as ringing a bell.

We recommend that changing gear be effected either when pressure on the pedals is relaxed or when free-wheeling. wheeling.

The illustration shows the Bracket Gear detached from the axle, and the letters show the various parts which are affected when the gear is fitted, or when adjustment is necessary.

Is necessary.

The Trip "C" controls the driving Pawl "D." When the normal gear is in use, this driving Pawl "D" is in engagement with a rack cut in the chain wheel, and the whole gear drives solid just like an ordinary chain wheel, but when the low gear is required the trip "C" depresses the Pawl "D" and brings the low gear into action.

When adjustment is necessary the gear should be in normal position, the nut "A" should be slacked off, and nut "B" screwed down until the trip "O" clears the Pawl "D" by about ½ in. Afterwards the nut "A" should be locked to nut "B," and any slack in the operating cable taken up by slightly moving the clip along the top tube.




Before purchasing your Bicycle, we ask you to carefully peruse this Catalogue, which contains a full range of Bicycles of the highest grade, built to suit every type of rider, at prices which are the lowest possible consistent with the use of materials of the highest grade and workmanship of the best class. James Bicycles are not "push-bikes." They require very little effort to propel for the reason that they are carefully and truly built in true and permanent alignment. Your cycling will remain a lasting pleasure if you ride a James Bicycle.

Dealers throughout the world will supply.

FULL RANGE ALWAYS ON VIEW AT OUR

LONDON SHOWROOMS: 21/22, Holborn Viaduct, E.C.1

THE FAMOUS JAMES CYCLES



MANUFACTURED SOLFLY BY

THE JAMES CYCLE CO. LTD. GREET, BIRMINGHAM

Telephone: 129 Victoria.

Telegrams: "Blcycles, Birmingham."

LONDON SHOWROOMS:

21 & 22, HOLBORN VIADUCT, E.C.I

Telephone: 1914 Central and 7449 City.


Telegrams: "Jacycom, London,"

DUBLIN DEPOT -

106/107, MID. ABBEY STREET

Telephone: 1764 Dublin

Telegrams : " Huct. Dublin."



In introducing our latest range of Cycles, it is our desire to convince the reader of their outstanding value. Our long and continuous connection with Cycle making is as old as the pastime itself, and the rider of a "James" machine is assured that he has the advantage of such experience, which accumulates in an organisation where only the BEST of everything is used.

It is now, as always, our policy to produce *quality* machines, built up to a high standard rather than *quantity* machines built down to a low and doubtful economic price by so-called mass production methods.

The models described herein cover a full range, from Juvenile machines through a comprehensive series of Ladies' and Gents' Models, to the superb Model-de-Luxe, which is without doubt the finest bicycle manufactured. The requirements of Tricycle and Tandem riders are also adequately provided for.

We would direct the reader's special attention to the Two-speed Bicycle (The Machine with the "Golden Ring"), which is fully described on the inner pages of the cover. There is no doubt this is the greatest Bicycle value ever offered to the Public.


A resumé of our productions would not be complete without reference to our "Ace" series of Road Racing Bicycles and Lightweights. The success of many riders, both professional and amateur, who have chosen one of these popular types, testify to their particular merit for touring or road and path racing purposes, and we unhesitatingly recommend them to the discriminating cyclist who appreciates the finer points of a really high-grade machine.

We have always been proud of the fact that "James" productions are "James" through and through. Every part of every machine is designed and made in our own works, and the high reputation for consistent quality during the past fifty years is due to the care and thoroughness of our manufacturing methods from start to finish.

We particularly draw your attention to our very fully equipped London Showrooms, 21-22, Holborn Viaduct, E.C., where a full range of all our latest models may be seen.

SPECIAL JAMES FEATURES

Details by which the James excels





Chain Wheel.

(Registered Design.)

One of the most arresting features of a "James" bicycle is the Chain Wheel. Apart from its attractive design, it will be noticed that it is light, rigid, and strong. The utmost care has been expended on making it a smooth working component, as it is the primary unit in the transmission of the rider's power. All "James" Chain Wheels have their teeth cut accurately by milling with the correct form cutter—not pressed out, as is usual with cheap chain wheels.



Patent Oil-retaining Stud Hubs.


The Stud Hubs, as illustrated, obtainable only on "James" machines, are fitted to Standard

Models and upwards. The straight spoke, which eliminates the bend of the spoke at the head, provides a direct tangential pull from the hub to the rim. This ensures a wheel of extreme rigidity, and provides absolutely direct tension on each spoke, ensuring a true wheel at all times. The bearings are oil-retaining and dustproof, of best possible material and design.





Set



The head set here illustrated is standard throughout the "James" range. It has a distinctive neatness all its own, whilst its mechanical efficiency is beyond reproach. The section also shows clearly the method of adjusting the handlebar to suit the individual rider.

LADY'S MODEL-DE-LUXE ROADSTER



Model No. 13

SPECIFICATION:

FRAME	***	Low built, 22 in., 24 in., and 26 in. Built with best Butt-ended Weldless High Carbon Steel Tube, correctly mitred at joints.
WHEELS		28 in. × 14 in., Black Centres, Lined Gold.
HUBS		James Patent Stud, straight-pull spokes, double-butted.
TYRES	6.4	Dunlop, "Fort Dunlop" (Translucent), 28 in. × 11 in.
GEAR		James Patent Bracket Two-speed Gear, or Three-speed Hub Gear to order.
FREE WHE	EL	James Special Full Ball-Bearing.
CHAIN		Hans Renold, 1-in. Pitch Roller, running in Oil-bath Gear Case.
GEAR CAS	E	James Registered Oil-bath. Detachable from frame.
HANDLEBA	R	Raised as illustrated, or option, with Brazed Brake Lugs.
BRAKES		James Front and Rear Rim, with Brazed attachments to
BHAKES	33	Frame : simple and efficient adjustment for wear.
SADDLE		Lady's Brooks, B85.

Best quality Steel Car Section, with Double Stays. James Aluminium. James Solid Centre Divided Rubbers. James Solid Centre invided Rubbers, Square Toolbag and necessary Spanners, Oiler, large Celluloid Inflater. Approved Rear Reflector. Black Enamel, on rust-proofed surface, lined fine burnished Gold. Usual parts heavily Nickel-plated on Copper, or All-Black All-Weather Finish throughout optional. EQUIPMENT FINISH ..

Price £12 : 0 net cash

Easy Payment Terms - 12 Payments of £1

This bicycle is of the highest possible grade, requiring a minimum of attention and physical effort to ride. Of distinctive design and superb finish with perfect equipment it typifies the height of refinement in cycle construction. This model is designed to meet the demand of discriminating riders for a machine where material and workmanship of the best quality is essential.

GENTLEMAN'S MODEL-DE-LUXE ROADSTER



Model No. 12

SPECIFICATION:

FRAME	Low built, 22 in., 24 in., and 26 in. Built with best Butt-ended Weldless High Carbon Steel Tube, correctly mitred at joints.
WHEELS	28 in. × 1½ in., Black Centres, Lined Gold.
HUBS	James Patent Stud, straight-pull spokes, double-butted.
TYRES	Dunlop, "Fort Dunlop" (Translucent), 28 in. x 14 in.
GEAR	James Patent Bracket Two-speed Gear, or Three-speed Hub
MHAN	Gear to order.
FREE WHEEL	James Special Full Ball Bearing.
	James Special Full Ball Bearing.
CHAIN	Hans Renold, 4-in. Pitch Roller, running in Oil-bath Gear Case.
GEAR CASE	James Registered Oil-bath. Detachable from frame.
HANDLEBAR	Raised as illustrated, or option, with Brazed Brake Lugs.
BRAKES	James Front and Rear Rim, with Brazed attachments to
	Frame : simple and efficient adjustment for wear.
SADDLE	Brooks B90/1.
MUDGUARDS	Best quality Steel Car Section, with Double Stays.
	pese quality Steet Car Section, with Double Stays.
REAR CARRIER	
PEDALS	James Solid Centre Divided Rubbers.
EQUIPMENT	Square Toolbag and necessary Spanners, Oiler, large Celluloid
The state of the s	Inflater. Approved Rear Reflector.
FINISH	Black Enamel, on rust-proofed surface, lined fine burnished
· miletim in	Gold. Usual parts heavily Nickel-plated on Copper, or All-
	Died 11 Wester Resviry Nicker-placed on Copper, or All-
	Black All-Weather Finish throughout optional.

Price £12:12:0 net cash

Easy Payment Terms - - 12 Payments of £1 : 5 : 0

This model is supreme for quality, and the frame is of special design. It is built with a low bracket to provide a low and easy riding position. The rear portion is built from tapered tubes, and has a solid seat cluster set. This model may also be supplied with 26-in. wheels and low-built diamond frame, making a very desirable low-built full roadster of minimum weight.

LADY'S IMPERIAL LIGHTWEIGHT



Model No. 11.

SPECIFICATION:

FRAME		Low built, 20 in., 21 in., 22 in., 23 in., and 24 in. Special Light
		Type, with Parallel Top Tube, Round Section tapered Front Fork, Seat Stays, Brazed at Seat Lug. Usual curved Top Tube can be supplied if ordered.
WHEELS		26 in. × 14 in. "Engrick" Steel Rims.
TYRES		Dunlop or Constrictor, Road Racing, 26 in. × 17 in.
		James Patent Stud, Straight Pull, 16/18 Gauge Spokes, Laced
HUBS	***	and Soldered at Crossings.
HANDLEBA	R	Raised Pattern Forward V or optional.
BRAKES		James Front and Rear Caliper Rim, quickly detachable.
		Chain Wheel, Flanged Pattern, detachable from Crank. Bracket
GEAR	***	Two-speed, £1 extra.
CRANKS	2224	61 in. or 7 in., to order.
CHAIN	100	Hans Renold, 1-in. Pitch Roller.
SADDLE		Brooks B10, Enamelled, or Resilion Model to order.
	-	
MUDGUARI		Narrow Section, Steel.
EQUIPMEN	т	Toolbag and necessary Spanners, Oiler, large Celluloid Inflater. Approved Rear Reflector.
FINISH	4.64	Four Coats of Black Enamel. Bright Parts heavily Nickel- plated. Gold leaf head, no lines.

Price £10 : 10 : 0 net cash

Easy Payment Terms - - 12 Payments of £1:1:0

This model is produced as light as possible with all necessary fittings, but additional equipment such as speed gears, etc., are dispensed with. These, however, may be fitted if desired. The conventional curved top tube can be supplied if required without extra charge. This model is specially recommended as a light tourist's machine.

GENTLEMAN'S IMPERIAL LIGHTWEIGHT



Model No. 10

SPECIFICATION:


FRAME	***	Low built, 20 in., 21 in., 22 in., 23 in., and 24 in. Special Light
		Type, with Parallel Top Tube, Round Section tapered Front Fork, Seat Stays, Brazed at Seat Lug.
WHEELS		26 in. × 1; in. "Endrick" Steel Rims.
TYRES		Dunlop or Constrictor, Road Racing, 26 in. × 14 in.
HUBS		James Detent Start Startely Tall 12 16 16 X 1 1 11.
100	***	James Patent Stud, Straight Pull, 16/18 Gauge Spokes, Laced and Soldered at Crossings.
HANDLEBA	D	Policed or Plat Pottsings.
BRAKES		Raised or Flat Pattern Forward V or North Road optional.
	***	James Front and Rear Chimer Rim, quickly detachable
GEAR	***	Chain wheel, Flanged Pattern, detachable from Crank Bracket
		Two-speed, £1 extra.
CRANKS		6j in. or 7 in., to order.
CHAIN		Hans Renold, 1 in. Pitch Roller.
SADDLE		Brooks Did Brooks I no Files
MUDGUARI	96"	Brooks B10, Enamelled, or Resilion Model to order.
		Narrow Section, Steel.
EQUIPMEN	Time	Toolbag and necessary Spanners, Oiler, large Celluloid Inflater.
		Approved Rear Renector.
FINISH		Four Coats of Black Enamel. Bright Parts heavily Nickel-
		plated. Gold leaf head, no lines.
		NOTICE OF THE PROPERTY OF THE

Price £10 : 10 : 0 net cash

Easy Payment Terms - - 12 Payments of £1:1:0

These models are designed to meet the modern demand for a really light, low-built roadster, which embodies all those essential details necessary for the comfort and convenience of the cyclist who from experience knows what is required in a high-grade lightweight. The C.T.C. rider will find this model to include all those features which have earned the approbation of "real cyclists."

LADY'S STANDARD ROADSTER



Model No. 8

SPECIFICATION:

22 in., 24 in. and 26 in. sizes, built of best Weldless Steel Tubc. 28 in. × 1½ in. Enamelled Centres, lined Red. James Patent Stud Pattern. Straight pull tangent Spokes. Dunlop roadster, 28 in. × 1½ in. Raised as illustrated, with Brazed Plate Brake Lugs. James Frent and Rear Rim with Brazed Fittings on Frame RAME ... NHEELS HUBS and Fork.

Brooks B75 or Lycett L19 Three-coil Enamel Springs.
63 in. 64 in. Cranks. Bracket Two-speed, £1 extra. SADDLE GEAR James Full Ball Bearing. Hans Renold, ‡ in. Pitch. James Divided Rubber. FREE WHEEL CHAIN ... PEDALS Full Metal detachable, as illustrated.
Double Stay Pattern, Car Section.
Toolbag and necessary Spanners, Oiler, Celluloid Inflater,
Approved Rear Reflector. GEAR CASE MUDGUARDS EQUIPMENT... Best Black Enamel on rust-proofed surface, Lined fine Gold, Bright Parts heavily Nickel-plated. All-Black All-Weather finish optional. FINISH ...

Price £7:5:0 net cash

Easy Payment Terms - - 12 Payments of 14/6

The lady cyclist can find no better value for money than is offered in the James "Standard" Bicycle. "James Quality"—perfect workmanship and finish, at a price which places it within reach of most bicycle buyers, it may be relied upon as a perfect first quality light running machine at a very reasonable price.

GENTLEMAN'S STANDARD ROADSTER



Model No. 7

SPECIFICATION:

FRAME	22 in., 24 in. and 26 in. sizes, built of best Weldless Steel Tube.
WHEELS	28 in. × 14 in. Enamelled Centres, lined Red.
HUBS	James Patent Stud Pattern. Straight pull tangent Spokes.
TYRES	Dunlop roadster, 28 in. × 15 in.
HANDLEBAR	
	Raised, as illustrated, with Brazed Plate Brake Lugs.
BRAKES	James Front and Rear Rim, with Brazed Fittings on Frame and Fork.
SADDLE	Brooks B75 or Lycett L19 Three-coil Enamel Springs.
GEAR	Gent's 68 in. 7 in. cranks. Bracket Two-speed, £1 extra.
FREE WHEEL	James Full Ball Bearing.
CHAIN	Hans Renold, 1 in. Pitch.
PEDALS	James Divided Rubber.
MUDGUARDS	Double Stay Pattern, Car Section.
EQUIPMENT	Toolbag and necessary Spanners, Oller, Celluloid Inflater,
	Approved Rear Reflector.
FINISH	
	Bright Parts heavily Nickel-plated. All-Black All-Weather

Price £6: 17: 6 net cash

Easy Payment Terms - - 12 Payments of 13/9

The specification of this model includes all the standard James features such as stud hubs, straight tangent spokes, etc. For those who require a perfectly free-running, strong and reliable machine, in which all equipment and fittings are of the highest standard quality, at a reasonable figure, there is no machine which can compare with "The James Standard."

LADY'S COMET ROADSTER



Model No. 32

SPECIFICATION:

22 in., 24 in., and 26 in. Built of best quality Weldless Steel FRAME ... Tupe.
28 in. × 1½ in., Enamelled Centres, Lined Red.
James Flanged Pattern.
Dunlop roadster, 28 in. × 1½ in.
As illustrated, with Brazed Plate Brake Lugs.
Rolling Lever, Front and Rear Rim.
Brooks or Lycett Three-coil Enamelled Springs.
Lady's 63 in. 6½ in. cranks. Bracket Two-speed, £1 extra,
Full Ball Bearing.
Lin. Pitch Beller. Tube. WHEELS

HUBS

BRAKES

SADDLE FREE WHEEL

in. Pitch Roller. Leatherette, with Celluloid Panels, or Plain Metal Chain Cover. Single Stay Pattern. CHAIN GEAR CASE MUDGUARDS

Single Stay Fatters.

Toolbag and necessary Spanners, Oller, Celluloid Inflater and Clips. Approved Rear Reflector.

Black Enamel, Lined Bronze and Red, Bright Parts Plated.

All-Black All-Weather finish optional. EQUIPMENT ...

FINISH ...

6 net cash Price £5

12 Payments of 11/9 Easy Payment Terms

Though offered at a very low price, we can recommend this machine with perfect confidence for those who require a perfectly free-running, strong and reliable blcycle at a low figure. There is no machine to compare with "The James Comet" for quality of specification and value for money.

GENTLEMAN'S COMET ROADSTER



Model No. 31

SPECIFICATION:

FRAME... ... 22 in., 24 in., and 26 in. Built of best quality Weldless Steel Tube.

WHEELS ... 28 in. × 1½ in., Enamelled Centres, Lined Red.

James Flanged Pattern.

TYRES ... Dunlop roadster, 28 in. × 1½ in.

HANDLEBAR... As illustrated, with Brazed Plate Brake Lugs.

BRAKES ... Rolling Lever, Front and Rear Rim.

SADDLE ... Brooks or Lycett Three-coil Enamelled Springs.

GEAR ... Gent's 68 in. 7 in. cranks. Bracket Two-speed, £1 extra.

FIRE WHEEL

CHAIN ... Hall Bearing.

Jin. Pitch Roller.

Single Stay Pattern

Toolbag and necessary Spanners, Oiler, Celluloid Inflater and Clips. Approved Rear Reflector.

Black Lugs.

FINISH... Black Lugs.

Black Flandel, Lined Red.

But the decidence of the control of the contro

Price £5: 10: 0 net cash

Easy Payment Terms -

12 Payments of 11/-

The buyer who desires a strong and reliable cycle will secure excellent service from the James "Comet" models, as they are built with the same care and precision as other James models, and of excellent quality materials. The equipment includes fitments of good quality, which may be relied upon for hard service.

STANDARD LIGHT ROADSTER



Model No. 9

SPECIFICATION:

FRAME	23 and 25 in. sizes, built of best Weldless Steel Tube.
WHEELS	26 in. × 1½ in. Enamelled Centres, lined Red.
HUB\$	James Patent Stud Pattern. Straight pull tangent Spokes.
TYRES	Dunlop roadster, 26 in. × 1½ in.
HANDLEBAR	Raised, as illustrated, with Brazed Brake Lugs. North Road
	Drop Bar optional.
BRAKES	James Front and Rear Rim, with Brazed Fittings on Frame and Fork.
SADDLE	Brooks B18 Enamel Springs.
GEAR	69 in. 7 in. Cranks. Bracket Two-speed, £1 extra.
FREE WHEEL	James Full Ball Bearing.
CHAIN	Hans Renold, † in. Pitch.
PEDALS	James Rat Trap.
MUDGUARDS	Double Stay Pattern, Car Section.
EQUIPMENT	Toolbag and necessary Spanners, Oiler, Celluloid Inflater. Approved Rear Reflector.
FINISH	Best Black Enamel on rust-proofed surface, Lined fine Gold,

Price £6: 17: 6 net cash

Easy Payment Terms - - 12 Payments of 13/9

This model is offered in two forms, either as illustrated above with a sloping top rail or built with a parallel top rail and low-built bracket. In this latter form it makes a very attractive mount of the "Cob" type, which will be much appreciated by riders who use their machines in traffic. All the usual standard James equipment is incorporated in this model.

COMET LIGHT ROADSTER



Model No. 33

SPECIFICATION:

FRAME	23 in. and 25 in. Built of best quality Weldless Steel Tube.
WHEELS	26 in. × 1½ in., Enamelled Centres, Lined Red.
HUBS	James Flanged Pattern.
TYRES	Dunlop roadster, 26 in. × 11 in.
HANDLEBAR	As illustrated, with Brazed Plate Brake Lugs. North Road
	Drop Bar optional.
BRAKES	
CARRIE	Rolling Lever, Front and Rear Rim.
SADDLE	Brooks or Lycett Enamelled Springs.
GEAR	69 in. 7 in. Cranks. Bracket Two-speed, £1 extra.
FREE WHEEL	Full Ball Bearing.
CHAIN	in. Pitch Roller.
PEDALS	Rat Trap.
MUDGUARDS	Single Stay Pattern.
EQUIPMENT	Toolbag and necessary Spanners, Oiler, Celluloid Inflater and
	Clips. Approved Rear Reflector.
FINISH	Black Enamel, Lined Bronze and Red, Bright Parts Plated.
1.000 TO TO TO THE STATE OF THE	- Taris Plated.


Price £5: 10: 0 net cash

Easy Payment Terms - - 12 Payments of 11/-

The machine illustrated above substantially follows the same specification as the "Comet" Roadster, illustrated on page 11, but it is built with a sloping top rail and 26 in, wheels. As an alternative it can be supplied with a North Road drop bar. It is a very popular type for those who desire a light-running Light Roadster with good hard-wearing qualities.

SPECIAL FEATURES OF ACE MODELS

Front view of Ace of Trumps Model.



original chain adjustment. This is obtained by mounting an accurately machined serrated plate on the forward opening fork end which is adjustable independently. The wheel is held in position by lever nuts, which are also provided with serrations which accurately fit those on the sliding plate.

The side view of the head indicates the fine workmanship employed in the lightening of the head lugs, and also indicates the method of adjusting handle-bars; if it is preferred the tubular curved forward stem can be supplied instead of the lap joint as illustrated.


The illustration shows a view of the Ace of Trumps machine and indicates the clean design of the machine from an end-on view. The cutaway lugs and transfer on the gold head make a neat ensemble.

Front Forks are round section throughout, well linered at the crown; whilst the ends are machined from solid steel stampings having a mudguard attachment integral therewith.

The frame is built from the highest grade steel tubes, double butted, and correctly mitred at all joints. The wheel base is 42½ in., and the height of bracket 10½ in. The weight of the stripped Path Racer is 18 lbs., and the weight of the Road Racer varies according to equipment, from about 25 lbs.


The "James" drop-out, as illustrated, is a neat yet very efficient device for a quick removal and replacement of the rear wheel so as to provide alternative gears. With the "James" drop-out, an alteration of 1, 2, or more teeth is available. The "James" dropout provides an original arrangement for the

Side view of Head.






The illustration indicates a view looking directly down over the handlebar, and shows the shape and relative width of the bar.




Seat Stays.

On the left the illustration is taken from the rear of the machine, and indicates the seat stays, showing clearly a brazedup seat cluster set which was introduced by the James Cycle Co., and also the "James" Caliper brake, which is light yet powerful. The chain peg is also apparent on this illustration.

The illustration on the right hand of the page shows a view taken from the underside of the machine of the chain stays and indicates their extreme rigidity. These chain stays are tapered tubes from the bracket to the steel fork ends, and are free from cranks and depressions of any kind. Consequently every ounce of power put into the pedals is transmitted to the back wheel without any loss occasioned by the whipping of the rear stays.







ACE OF TRUMPS ROAD RACER



Model No. 19A

SPECIFICATION:

FRAME		20 in., 21 in., 22 in., 23 in., and 24 in. Special Light Racing Type with Parallel Top Tube, Round Section tapered Front
		Fork, Seat Stays, Brazed at Seat Lug, Cutaway Lugs.
WHEELS		26 in. × 1½ in. "Endrick" Steel Rims. Cane colour.
	0.00	20 III. A 14 III. Million Scott Itims. Calle Glight.
SPOKES	6.616	Double-butted, 16/18 Gauge, Laced and Soldered at Crossings.
TYRES	100	Dunlop or Constrictor, Road Racing, 26 in. × 11 in.
REAR HUB	111	Special Pattern, fitted with Solid Spindle, Forward Quick
mean nou	55.5	Balance and District Concepts and side for settle Quick
		Release, and Driving Sprocket each side for quick change of
		gear. Fixed Sprockets. One Free Wheel optional.
HANDLEBA	R	Marsh Pattern, with Forward adjustable Extension, or alterna-
	233000	tive, Constrictor Anti-shock Grips.
BRAKE		James Caliper Type, to Rear Wheel only.
		total Chair When I War and Delical Williams
GEAR	640	48th Chain Wheel, Flanged Pattern, detachable from Crank.
		Rear Sprockets, 16th and 18th.
CRANKS		61 in. or 7 in. to order.
CHAIN		Hans Renold, & in. Pitch Roller.
SADDLE	414	Brooks B17 Champion or Resilion Model to order.
MUDGUARD	วธ	Celluloid, quickly detachable.
EQUIPMEN	T	Toolbag and necessary Spanners, Oiler, Celluloid Inflater.
	-	Approved Rear Reflector. Lamp Bracket brazed on front fork.
		approved real remedicit. Lamp Dracket orazed on Front forg.
FINISH		Four Coats of Black Enamel. Bright Parts heavily Nickel-
		plated. Geld leaf head.

Price £10 : 10 : 0 net cash

Path Model, No. 19, same price.

Easy Payment Terms - - 12 Payments of £1:1:0

This is an ideal machine for fast road riding. It embodies every feature which, in the opinion of experts, conduces to a light and lively sweet running machine. The Path model, which is built on identically the same lines and weighs about 18 lbs., is the chosen mount of champions of national and international repute, who have accomplished many world's records thereon.

CLUBMAN ACE ROAD RACER



Model No. 34

SPECIFICATION :

FRAME	20 in., 21 in., 22 in., 23 in. and 24 in. Special Light Type, Parallel Top Tubes, D to Round Tapered Front Fork, Round Section
	Seat Stays, Brazed at Seat Lug, Cutaway Lugs,
WHEELS	26 in. × 1; in. " Endrick " Steel Rims, cane colour,
TYRES	Dunlop, Clipper Sports, 26 in. × 1½ in., wired-on.
FRONT HUB	James Flange.
REAR HUB	Special Pattern, fitted with Quick Release. Driving Sprocket
	each side for quick change of gear. Fixed Sprockets giving
	close or wide ratios. Free Wheels, 3/6 extra.
HANDLEBAR	Marsh Pattern, on adjustable extended lug.
BRAKE	James Caliper Type, to Rear Wheel only,
GEAR	44th or 48th Chain Wheel, Fixed Gear, 61 in Cranks.
CHAIN	Hans Renold, 1 in. Pitch.
	Brooks B18 or racing pattern to Gent's optional.
MUDGUARDS	Steel, Lightweight.
EQUIPMENT	Toolbag and necessary Spanners, Oiler, Celluloid Inflater.
	Approved Rear Reflector.
FINISH	Four Coats Black Enamel. Gold Head. Bright Parts heavily
ricion	Nickel-plated.
	Mickel-pineou.

Price £8:0:0 net cash

Lady's Model, No. 35, same price (as illustration on page 19).

Easy Payment Terms

12 Payments of 16/-

The Clubman Ace Road Racer, whilst not including the high refinements in detail of specification as the "Ace of Trumps," is still an excellent mount for the clubman, which may be relied upon to give unfailing service. The frame is built on the same lines as the "Ace of Trumps" machine, and examination of the specification will show its wonderful value.

ACE RECORD ROAD RACER



Model No. 36

SPECIFICATION :

21 in., 23 in. and 25 in., Special Light Type, Parallel Top Tubes, Round Section Seat Stays, Brazed at Seat Lug. FRAME ...

WHEELS

Top Tubes, Round Section Seat Stays, Brazeu as Seat Bug, Cutaway Lugs.

26 in. × 1‡ in. "Endrick" Steel Rims, cane colour.
Dunlop Clipper, 26 in. × 1‡ in., wired-on.
James Flange.

Special Pattern, fitted with Quick Release. Driving Sprocket each side for quick change of gear. Fixed Sprockets giving close or wide ratios. Free Wheels, 3/6 extra.

Marsh Pattern, on fixed extended lug. Adjustable Extension 8/2 extra. HANDLEBAR ...

5/- extra.

5/- extra.

James Caliper Type, to Rear Wheel only

44th or 48th Chain Wheel, Fixed Gear. 6½ in Cranks.

Hans Renold, ½ in. Pitch.

Narrow Racing pattern optional.

Steel, Lightweight. BRAKE ... GEAR

GEAR ...

SADDLE MUDGUARDS

Toolbag and necessary Spanners, Oiler, Celluloid Inflater. Approved Rear Reflector. Four Coats Black Enamel. Cream Head. Bright Parts heavily EQUIPMENT ...

FINISH ... Nickel-plated.

Price £6: 15: 0 net cash

Easy Payment Terms

12 Payments of 13/6

This model has been designed to provide a Road Racing machine at a popular price which would embody all the particular features which are demanded by clubmen. The frame is rigidly built with a solid seat cluster set, and the whole machine is built so as to adequately withstand any amount of hard wear.

LADY'S ACE RECORD ROAD RACER



Model No. 18

SPECIFICATION:

FRAME	20 in., 22 in. and 24 in., Special Light Type, Parallel
	Top Tubes, Round Section Seat Stays, Brazed at Seat Lug.
	Cutaway Lugs.
WHEELS	
TYRES	Dunlop Clipper, 26 in. × 11 in., wired-on.
FRONT HUB	James Flange.
REAR HUB	Special Pattern, fitted with Quick Release. Driving Sprocket
nean nos	special factority itted with Quick Release. Driving Sprocket
	each side for quick change of gear. Fixed Sprockets giving
	close or wide ratios.
HANDLEBAR	North Road, either Dropped or Raised, to order.
BRAKE	James Caliper Type, to Rear Wheel only.
GEAR	44th Chain Wheel, Fixed Gear. Free Wheels, 3/6 extra.
CHAIN	Hans Renold, 1 in. Pitch.
PADDLE	Four-wire Road Racing.
MUDGUARDS	
	Steel, Lightweight.
EQUIPMENT	Toolbag and necessary Spanners, Oiler, Celluloid Inflater.
	Approved Rear Reflector.
FINISH	Four Coats Black Enamel. Cream Head. Bright Parts heavily
	Nickel-plated.

Price £6: 15: 0 net cash

Easy Payment Terms - - 12 Payments of 13/6

The machine illustrated above is listed to meet the demands of the sports girl who requires a light and rigid machine which provides the correct riding position for riders who indulge in fast road work or club runs. In details of specification it includes all features which are considered desirable for this type of machine.

LADIES' AND GENTLEMEN'S TANDEMS



Full Specification on application.

Model No. 24 MIXEDTANDEM


No. 24 Model £18:18:0 net cash

Easy
Payment Terms:
12 Payments of
£1:17:6

Model No. 23 CLUBMAN'S TANDEM

No. 23 Model £16:16:0 net cash

Easy Payment Terms: 12 Payments of £1:13:6



SPECIFICATION No. 23:

FRAME.—22 in. Front and Rear, or to order.
WHEELS.—26 in. × 14 in., Enamelled
Wood Colour. Rear Hub fitted with
Forward Quick Release Drop-out,
as Ace Models.
HANDLEBARS.—Marsh pattern on forward

HANDLEBARS.—Marsh pattern on forward adjustable lug.

TYRES.—Fort Dunlop translucent 26 in. × 1; in.

BRAKES.—Front and Rear. Caliper type.
Designed specially for tandem work.
SADDLES.—Brooks B18.
GEAR.—69 and 78, or to order.
CHAINS.—Hans Renold, † in. Pitch.
MUDGUARDS (optional). Best quality
Light Steel, with Double Stay.
FINISH.—Black Enamel, Bright Parts
heavily Nickel-plated.

The James Bracket Two-speed Gear may be fitted to above models at £1:10:0 extra.

The No. 23 Clubman Tandem has for years proved a very popular Road Racer model amongst clubmen, being particularly rigid and with a good variation of positions. This is the type of tandem equipped as a path machine which secured the following remarkable tandem records during 1928: All records from 51 to 100 miles, including 2 and 3 hour records; records from 31 to 35 miles, and from 39 to 42 miles; 1 hour tandem paced record—31 miles 470 yards; 1 mile flying start tandem record—1 minute 45 seconds.

LADIES' AND GENTLEMEN'S TRICYCLES



DE LUKE BACK AXLE

SPECIFICATION :

FRAME.—22 in. or 24 in. WHEELS.—26 in. × 1½ in. Enamelled Black Centres, Lined Red.

TYRES. — Dunlop Cord, 26 in. × 1; in. HANDLEBAR. — Raised.

as illustration, with Brazed

Plate Brake Lugs.

AXLE.—De Luxe,
brakes in axle box. Standard, Plain Free Wheel.

Wheel.

BRAKES.—De Luxe contracting Band Brakes in Axle. Standard, Front Hub Brake and Front Rim Brake.

SADDLE.—De Luxe, Brooks B75. Standard, Lycett's L20.

Gentleman's Model No. 25

Nos. 25 and 26 Models £25 : 0 : 0 net cash

Easy Payment Terms

- 12 Payments of £2": 10 : 0

SPECIFICATION: (contd.)

- Hans Renold, CHAIN. -

din. × in.

GEAR.—De Luxe, James
Bracket Two-speed, Stan-

dard Single Gear 62.

GEAR CASE.—De Luxe,
James Oil-bath, Standard
Chain Cover to Lady's
Model only.

MUDGUARDS,-Full Set.

including Side Guards. EQUIPMENT. — Toolbag

and necessary Spanners, Initater, Oiler, approved Rear Reflector, etc. FINISH.—Black Enamel on Rustproof Surface. De Luxe, Lined Fine Gold. Standard, Lined Red and Bronze.



Lady's Model No. 28

Nos. 27 and 28 Models £16 : 16 : 0 net cash

Easy Payment Terms

. . 12 Payments of £1:13:6

BOYS' AND GIRLS' BICYCLES AND TRICYCLES

"Brownie" de Luxe Model (Registered)

This model has several refinements over the Standard model. It is built in two sizes, 14 in. and 17 in. seat tubes, which give a reach of 21 in. and 24 in. when the saddle is in the lowest position. Each may be adjusted 4 inches higher if necessary. The wheels are 14 in. diameter and are fitted with

"Sorbo" unburstable tyres. A large size three-coil saddle is fitted. The front rim brake-work is very reliable and strong. An efficient chain guard is fitted and a combined carrier and stand. Finished in superfine black stoved enamel, lined in red and gold, with bright parts heavily nickel-plated.

£5:0:0

Supplied with pneumatic tyres at the same price.

Easy Payment Terms: £5 0 0 model: 12 monthly instalments of 10/- each.

"Brownie" Standard Model (Registered)
This model provides the natural step towards riding an ordinary bicycle. It has ball bearings throughout, including bottom bracket wheels, steering head and pedals. The frame is built in 14 in. and 17 in. sizes, with 14 in. wheels, and is adjustable in the same way as the de luxe model. An adequate front rim brake is fitted. The tyres are moulded cushion type, and a comfortable three-coil saddle is fitted. The machine is finished in superfine black enamel, neatly lined in red, the usual bright parts being heavily nickel-plated.

£3:10:0

With Pneumatic Tyres, £4. Easy Payment Terms: 12 monthly instalments of 7/-.



BOYS' AND GIRLS' BICYCLES AND TRICYCLES

"Tweenie" Girl's Model
(Registered)

This model follows very closely on the lines of the machine described below, but is constructed so as to provide an open frame, which is preferred by many on account of the easier mounting and demounting facilities.

The wheels are 18 in. diameter, and are fitted with first-grade pneumatic tyres. The rims are nickel-plated, with a broad centre line of red, and finished in superfine black enamel, smartly lined in crimson and gold, all bright

parts heavily nickel-plated.

£5 : 0 : 0

Easy payment terms: 12 monthly instalments of 10/-.



"Tweenie" Girl's Model No. 47

"Tweenie" Boy's Model (Registered)

This has been designed to provide the link between the "Brownie" or "Pixie" type of machine and the standard type of bicycle.


With low-built frame, ensuring maximum strength with light weight. Ball bearings are fitted throughout. Made in one size only, 14 in. frame, which with 5 in. crank and large three-coil saddle, gives a minimum reach of 22 in., which is adjustable

to 26 in. Mudguards, a reliable front rim brake, and free wheel are included in the specification. Wheels 18 in. diameter, with firstgrade pneumatic tyres.

£5:0:0

Easy payment terms: 12 monthly instalments of 10/-.

"Tweenie" Boy's Model No. 46



With pneumatic tyres at the same price. Free Wheel (extra), 5/-. Easy payment terms : £5 10s. model: 12 monthly instalments of 11/-

fitted at a nominal extra charge.

Also made in No. 2 size, with 18 in. wheels, Price £6 15s., with pneumatic tyres.



"Pixie" Standard Tricycle (Registered)

This tricycle is quite suitable for the smallest children, and will withstand hard wear and give endless pleasure. The chain and working parts are fully protected, and the saddle and handlebars are both easily adjustable. The saddle has a range of adjustment varying from 17 in. to 21 in.,

measured from the pedal to the top of the saddle, to suit children from 4 to 7 years of age. The wheels are 14 in. diameter, fitted with moulded cushion tyres. A powerful rim front brake is fitted, ensuring perfect safety.

10 : 0

Free Wheel (extra), 5/-.

Easy payment terms: 12 monthly instalments of 9/-.

Also made in No. 2 size, with 18 in. wheels, price £5 5s., cushion tyres; pneumatic tyres £6 12s. 6d.

THE JAMES "MERCURY" MODELS FOR BOYS AND GIRLS



" Mercury" Girl's Model

James "Mercury" Cycles are built to the same standard of excellence as our adult cycles. Both boy's and girl's models are made in three sizes, with 16 in., 18 in., and 20 in. frames. The 16 in. and 18 in. frames are fitted with 24 in. wheels, and the 20 in. with 26 in. wheels. The reach with the saddle in its lowest position is

saddle in its lowest position is approximately: 16 in. frame, 25 in. reach; 18 in. frame, 27 in. reach; 20 in. frame, 30 in. reach; with an adjustment of 4 in. in each case.

£5:12:6

Easy payment terms: 12 monthly instalments of 11/3.

"Mercury" Boy's Model

The boy's model follows identically the specification described above, except that it is built with the usual diamond frame. Both models are equipped with two rim brakes and free wheel.

Attractively finished in superfine black enamel, smartly lined in red. The usual bright parts heavily nickel-plated; may be

supplied in all-black, allweather finish, without extra charge. Dunlop first-grade pneumatic tyres are fitted, and the equipment includes the necessary pump, tools and oiler.

£5:5:0

Easy payment terms: 12 monthly instalments of 10/6.




THE FAMOUS JAMES CARRIER BICYCLES



£10 : 10 : 0 net cash Easy Payment Terms: 12 Payments of £1:1:0



0 : 0 net cash Easy Payment Terms: 12 Payments of £1:4:0



Model D3

ABRIDGED SPECIFICATION :

FRAME-Extra strong, 23 in. Standard.

FORK-Girder Pattern, strengthened throughout to carry heavy loads. CARRIER-All Tubular, built integral

CARRIER—All Tubular, bulls integral with frame. (Does not move with the steering.)

BASKET—22 in. × 16 in. × 9 in.

WHEELS—26 in. × 1½ in.

TYRES—Heavy Clipper Carrier, 26 in. × 1½ in. Wired on.

HUBS—Special Heavy Carrier Pattern, Interchangeable Bearings.

HANDLEBAR—Raised, asillustrated. HANDLEBAR-Raised, as illustrated,

22 in. wide, giving perfect control, Brazed Plate Lugs, Rubber

Grips.

Grips.

BRAKES—"James" Front and Rear
Rim, Rolling Levers.

SADDLE—"Lycett" L.39 Girder

Enamelled Springs. Pattern, Enamelled Springs.

GEAR-57, or lower, if desired, for hilly districts.

FREE WHEEL-Full Ball Bearing.

CHAIN-Carrier, Heavy Pattern,

MUDGUARDS—Extra strong and wide, Double Stay Pattern, with Bridges.
PEDALS—Wide, Heavy Rubber,

Single Block.

FINISH—Black Enamel all over, on specially prepared rustproof surface.

NAME PLATES-Metal Detachable -writing in white, 4/- per dozen letters.


D2 MODEL. Similar in design to the D1 Model, but also provided with a carrier at the back. This machine may be ridden by a messenger of either sex.

D3 MODEL. Similar design to D1 Model, with carrier rigid with frame. girder front forks are fitted to this model.


£9:0:0 net cash

Easy Payment Terms: 12 Payments of 18/-

THE FAMOUS JAMES CARRIER TRICYCLES.



Easy Payment Terms: 12 Payments of £3:0:0



SPECIFICATION:

FRAME ...

TYRES ...

SADDLE BRAKES

22 in. The Ball Bearing Steering Head is heavily reinforced, and provision is made for lubrication.

Heavy Dunlop Carrier, 26 in. × 1½ in.

Special strong 'Lycett' L.39/2 Girder, with large Toolbag.

Very powerful, hand-applied to both Front Wheels, with lock, also Rear Rim Type.


Very strong Frame of Seasoned Oak, armoured with metal.

Curved Roof of Sheet Metal. Size: Outside, 32 in. long × 24 in. wide × 24 in. high, fitted with Top Ralls. Large Door Sheet Metal armoured, on Oak Frame. Weather-proof Beading all round. Strong Hinges and Lock.

Box painted "James" Brown, two shades. Frame, Wheels, and all Cycle Parts, Superfine Black Enamel on prepared Rust-proof surface. BOX

FINISH ...

proof surface. May be supplied. Size: 28 in. \times 20 in. \times 1½ in. deep. Complete with runners at 10/- each extra. TRAYS ...



A2 MODEL has been designed to suit those customers who prefer the load at the rear. The benefit of lighter steering and easier control is afforded by this design, whilst the carrier is considerably lighter than the Al Model. Any type of box may be supplied to suit customers' requirements.


Model A2 £25 : 0 : 0 net cash

Easy Payment Terms -- 12 Payments of £2:10:0

The James Patent Bracket Two-speed Gear may be fitted to any James Carrier. Price £1:10:0 extra.

For other types and full particulars see our separate Catalogue for Carrier Cycles. THE JAMES CYCLE CO., LTD., LONDON AND BIRMINGHAM

THE FAMOUS JAMES MOTOR CYCLES



ABRIDGED SPECIFICATION.

ENGINE.—498 c.c., O.H.V. GEAR.—Four-speed.

TYRES.—Four-speed.
TYRES.—Dunlop 26 × 3.25.

TANK.-Welded Steel, Saddle type.

SADDLE. — Terry Multispring type.

æ15 : U : U

A 1. 500 c.c. O.H.V. TWIN.

Super Sports, 4-speed Gear. A De Luxe Super Sports Model for the connoisseur, guaranteed 80 m.p.h.



ABRIDGED SPECIFICATION.


ENGINE.—498 c.c., O.H.V. CLUTCH.—Hand operated Multi-plate.

TYRES. — Dunlop 27 × 2.75, W.O.

FORK.—Laterally Stayed Semi Rigid.

£85 : 0 : 0

A 12, 500 c.c. O.H.V. TWIN. SPEEDWAY MODEL.
The Supreme Dirt Track Racing Machine. The Choice of Champions.



ABRIDGED SPECIFICATION.

ENGINE.—498 c.c., S.V. GEAR.—Three-speed.

TYRES.—Dunlop 27 × 3, W.O.

TANK. — Welded Steel, Saddle type.

SADDLE.—Terry Multispring type.

£56 : 10 : 0

Standard Sports, 3-speed Gear. The Famous Standard Sports Twin. Champion of all classic Reliability Trials.

THE FAMOUS JAMES MOTOR CYCLES

ABRIDGED SPECIFICATION.


ENGINE.-349 c.c., O.H.V.

GEAR.—Three-speed.
TYRES.—Dunlop 27 × 3,
W.O.

TANK. — Welded Steel, Saddle type.

SADDLE. - Terry Multi- as spring type.

£48 : 0 : 0



A 4. 350 c.c. O.H.V. SINGLE.

Do Luxe Sports, 3-speed Gear. A Super Sports Machine of superlative value, guaranteed 65 m.p.h.

ABRIDGED SPECIFICATION.

ENGINE.—349 c.c., S.V. GEAR.—Three-speed.


TYRES.—Dunlop 27 × 3,

TANK. - Welded Steel,

Saddle type.

SADDLE. — Terry Multispring type.

£45 : 0 : 0



A 5. 350 c.c. S.V. SINGLE.

De Luxe Sports, 3-speed Gear. A de Luxe Motor Cycle of comprehensive specification, suitable for all-round use.

ABRIDGED SPECIFICATION.

ENGINE,-247 c.c., Two stroke.

GEAR .- Three-speed.

TYRES.—Dunlop 25 × 3, W.O.

TANK. — Welded Steel Saddle type.

SADDLE. — Terry Multispring type.


£36 : 0 : 0



A 11. 247 c.c. TWO-STROKE.

Standard Sports, 3-speed Gear. A Standard Sports Machine of outstanding value, robust and speedy. Reliable.

THE FAMOUS JAMES MOTOR CYCLES



ABRIDGED SPECIFICATION

ENGINE .- 172 c.c., Twostroke. GEAR.—Three-speed. TYRES.—Dunlop 25 × 3,


TANK. - Welded Steel-Saddle type.

SADDLE. - Terry Multispring type.

10:0

A 7. 172 c.c. TWO-STROKE.

De Luxe Super Sports, 3-speed Gear. A De Luxe Super Sports Machine, complete with every refinement, including electric light.



ABRIDGED SPECIFICATION.

ENGINE .-- 196 c.c., Twostroke.

GEAR .- Three-speed. YRES .- Dunlop 25 × 3,

TANK. - Welded Steel.

Saddle type. SADDLE. — Terry Multispring type.

10 : 0

A 8. 196 c.c. TWO-STROKE. Standard Sports, 3-speed Gear. A Machine of outstanding value and economy, with complete specification.



ABRIDGED SPECIFICATION.

ENGINE. -- 196 c.c., Twostroke.

GEAR.—Three-speed. TYRES. — Dunlop

375, W.O. Welded Steel, ANK. Saddle type. SADDLE. — Terry Multi-

spring type.

£26 : 15 : 0

A 9. 196 c.c. TWO-STROKE.

Utility Sports, 3-speed Gear. The last word in modern motor cycle utility and reliability.

EASY PAYMENT ORDER FORM

IMPORTANT.—To be filled up and signed in ink by the Customer in the presence of the Company's authorised Dealer.

Date.

To The JAMES CYCLE Co., Ltd.	, Greet, Birmingham. orm being completed to your satisfaction) one
"James" Cycle to the following specification	:
Model No.	
Payments to be made by me to the James Cycle C	o., Ltd., at Greet, Birmingham, by twelve monthly
payments of £ each.	
I hand you herewith £	which, if you accept this Order, his Order within twenty-one days is to be returned within seven days of due date, all the remaining payable by me. w are correct.
Signature of Customer. Signed	
Name in full { Mrs. Mrs. Miss } (In Block Letters)	
(In Block Letters)	
(an amount morning)	
	Age
Previous Address(In Full)	
Occupation	
Dealer must sign here	
Signature.	
	d to the James Cycle Co., Ltd., Birmingham.

GEAR AND HEIGHT TABLES

The Gear Table applies to Three-speeds, Two-speeds, and Single speed gears. For Single Gears the column marked "Normal" only applies.

For the James Patent Bracket Two-speed Gear the columns marked "Normal" and "Low" apply.

Gears for 26-in. Wheels.

No. of TEETH ON HUB	No. of Teeth on Chank Chain Wheel-1-In. Pirch.								
		44		48			52		
Coa.	LOW	NORMAL	нівн	Low	NORMAL	нідн	row	NORMAL	нісн
16 13 20	54 47 43	72 64 57	96 84 77	58 52 47	78 69 62	104 92 84	63 56 51	85 75 68	113 101 90

Gears for 28-in. Wheels.

Ne. of TRETH ON HUB Cog.	No. of Teeth on Chank Chain Wheel-1-in. Pitch.										
	44			48			52				
	Low	NORMAL	нын	LOW	NORMAL	нідн	LOW	NORMAL	нісн		
16 18 20	57 51 46	77 68 61	103 91 82	63 56 50	84 74 67	112 100 90	68 60 54	91 80 73	121 108 97		

The following Table is given as a guide for choice of suitable height of frame for various riders:—

Gentlemen.

Ladies.

HEIGHT OF	RECOMMENDED.	HEIGHT OF	HEIGHT OF FRAME RECOMMENDED.
5 ft. 10 in. and over 5 ft. 5 in. to 5 ft. 10 in. 5 ft. 2 in. to 5 ft. 5 in. Under 5 ft. 2 in	26 in. 24 in. 22 in. 20 in.	5 ft. 6 in. and over . 5 ft. 2 in. to 5 ft. 6 in Under 5 ft. 2 in.	

Extras.

	£	s.	d.	Onlinear Match Com Com	H.	d.
Heights of Frames other than listed		5	0	Ordinary Metal Gear Case where not specified	15	0
The James Patent Bracket Two-speed Gear	1	0	0	Tyres with headed edges "Roman" Aluminium Rims	2	
Three-speed Hub Gear			0	in place of Steel 1	- 1	0
Three-speed Coaster Hub Coaster Hub to any model	1	9	- 0	Valanced Mudguards in place of ordinary ones	5	0
Free Wheel in lieu of cog		3	6	Bluemel's Celluloid Mudguards (on "Clubman Ace" R R		
Oil-bath Gear Case to Gent's, where not specified	1	0	0	Model)	3	6
Oil-bath Gear Case to Lady's "Standard"		16	0	Adjustable Extension Handle- bars (Model 36)	5	0

THE "ACE" PAVEMENT CYCLE



SPECIFICATION:

FRAME—19 in, from Pedals to Saddle in lowest position, adjustable to 23 in. WHEELS—Full Ball Bearings, Plated Hubs.

TYRES—Large Section Cushion. PEDALS—Rubber with Ball Bearings. BRAKE—Rolling Lever Rim Brake.
SADDLE—Dunlop, waterproof.
FREEWHEEL—Best Quality.
FINISH—Best Brilliant Black Enamel,
lined bronze and red.

Price £2:3:6 net cash

Easy Payment Terms - 12 Payments of 4/6 each.

With Pneumatic Tyres £2:12:6

THE JAMES CYCLE CO., LTD., GREET, BIRMINGHAM LONDON SHOWROOMS - 21-22, HOLBORN VIADUCT, E.C.1

Ask for our fully-illustrated Catalogue of High-grade

"BROWNIE" PAVEMENT CYCLES

"PIXIE" PAVEMENT TRICYCLES

"SAMSON" JUVENILE TRICYCLES

"MERCURY" JUVENILE BICYCLES

ALL OF SUPERLATIVE DESIGN AND FINISH

Full range always on view at our

London Showrooms - 21-22, HOLBORN VIADUCT,

E.C.1

CYCLE AGENTS AND STORES THROUGHOUT

THE WORLD WILL SUPPLY

THE JAMES CYCLE CO., LTD., Works - GREET, BIRMINGHAM Estabe 1870

DISTINCTIVE IN DESIGN



DEPENDABLE IN SERVICE



CYCLES

SEE THE BICYCLE



THE GOLDEN RING

THE JAMES SYCLE CO. LID.

Head Office & Works: BIRMIN GHAM tondonShowrooms: 21322 HOLBORN VIADUCTice