

# Malaguti



Frame is duplex type with reinforcement at stress points and fitted with Marzocci hydraulic front forks. Rear suspension is a semi cantilever design permitting long travel and controlled by adjustable hydraulic units. Standard equipment includes kick start, crankcase shield, handlebar map-bag and ball ended levers with gaiters.

## CAVALCONE

### Specification

Model Classification:	Moped with restricted engine, Motor Cycle with unrestricted engine
Engine:	Morini 2 stroke with radial cylinder head
Capacity:	49.93 cc
Bore:	39 mm
Stroke:	41.8 mm
Compression ratio:	9.6:1
B.H.P.:	6.5@8500r.p.m. unrestricted 2@5000r.p.m. restricted
Carburettor:	Dellorto SHB 19/19 unrestricted Dellorto SHB 14/12 restricted
Fuel:	Petrol/oil Mixture@20:1 ratio
Transmission:	Helical primary drive, multi plate clutch and four speed foot change
Brakes:	120 mm single leading shoe front and rear
Tyres:	2.50x21 front, 3.00x18 rear
Ground clearance:	8 1/2"
Wheelbase:	50 1/2"
Overall length:	78"
Overall width:	33"
Saddle height:	33"
Weight:	159 lbs.

AGENT


The right is reserved by the manufacturer and the concessionaire, to change specifications or colours shown in this catalogue at any time.

**Malaguti** U.K.

HIGH STREET, RIPLEY, SURREY  
Machine Sales: Tel: (Ripley) 048-643-2909.  
Stores: Tel: (Ripley) 048-643-3170.



# IceniCAM Information Service



[www.icenicam.org.uk](http://www.icenicam.org.uk)