
Engine: 49.9 c.c. two-stroke. Aluminium cylinder with hard chromium plated bore. 2.0 B.H.P. ac 5,000 r.p.m. Enrichment valve for cold starting. Sediment trap incorporated in carburettor. Transmission: Infinitisty variable automatic gear change mechanism. Engline speed double action automatic dutch. Lightings Direct lighting from flywheel incorporating the distinct flower. Framer: Pressed steel beam pattern part incorporating relieves. Framer: Pressed steel beam pattern part incorporating relieves. Framer: Pressed steel beam pattern plated rims, vals gallons including reserve. Equipment; Electric horn, Toolbag, 1.3,8 gallons including reserve. Equipment; Electric horn, Toolbag, Toolkit, Inflator. Centre stand, Number plates. Mattress saddle. Fransis and Pressed steel stark. SPECIFICATION

the Ultramatic—the correct lower gear ratio is chosen. The Ultramatic makes 'crunching' acceleration. As road speed increases the Ultra-matic progressively selects a higher gear ratio for itself—and as the rider, or the gradient, slows A natural progression from the single-speed models—the Ultramatic is fitted with a completely automatic infinitely variable gear change, which makes light of hills and gives sparkling which makes light of hills and gives sparkling. xsT esenorud gnibuloni 6.91.962

## DITAMARTIU EMR




Engine: 49.9 c.c. two-strobe. Aluminium cylinder with hard chromium plated bore, 1.7 B.H.P. st. 5,000 r.p.m. Enrichment valve for cold plated bore, 1.7 B.H.P. st. 5,000 r.p.m. Enrichment valve for cold starting. Sediment trap incorporated in cabuneteer. Treatmission: Single-speed with engine speed double-section automatic clutch. Single-speed with engine speed double-section automatic clutch beadlamp with displant device. Rear lamp incorporating reflector. Persons tick displant device. Rear lamp incorporating reflector. 23 x 2 ryres, chrome plated rims, trust proof appless. Full width light Equipment and the speed speed of the speed o SPECIFICATION

All the advantages of the wonderful Runabout plus long travel—road smoothing telescopic forks, Extra large "dipping" headlamp and a dual-tone colour scheme make the Automatic the finest single speed moped available.

xaT əsadənu gnibuləni 8.91.461

### FINE AUTOMATIC MK,11





A simple twist of the wrist controls

- -Clutch
- -Acceleration
- -Gear change
- -Speed

through the Double-Action Clutch and

Automatic Gear Change





Cylinders are precision die-cast from light alloy for light weight with excellent heat conductivity. Hard chrome-plated bores for outstanding resistance to wear. Light alloy pistons have similar expansion characteristics to the cylinders to eliminate seizures. Accurately balanced and inate seizures. Accurately balanced and machined forged steel crankshafts and connecting rods with small and big-end bearings of caged needle roller type.

giving you-Simplicity and Safety.

# THE CHOICE IS YOURS

Any Raleigh owner will tell you why they bought their Raleigh Moped. They wanted independence without expense—they wanted motoring without parking problems—they wanted utter reliability but attractive styling and only Raleigh offered everything. The Raleigh bonus of automatic control tilts many people's choice, but a range which meets the differing needs and appeals of owners so perfectly can only come from a firm that studies its customers. All Raleigh Mopeds are backed by quality proved design and skilled workmanship famous the world over —YOU CAN RELY ON RALEIGH

**Buy your Raleigh** moped by

Any of these models can be yours for a small deposit, with the balance repayable over 18 or 24 months. Your Raleigh dealer will be happy to tell you about the Gradual Payments scheme.

gradual payments

Raleigh Industries' policy is one of continuous improvement, therefore, we reserve the right to alter the spelfications and prices without notice.














Tank-Top Carrier to fit all Rear Tank Models 15/6d.













Laminated Self-coloured Plastic Supplied complete with fittings RM6/8/9 models 78/6d. Robust, Lightweight, LEGSHIELDS




Small and lightweight. Made from aluminium alloy 5/8d. INFLATOR



Strong and waterproof each 25/7d. + 4/2d. P.T. Colourful PANNIER BAGS






button and fixing bracket 17/6d. Complete kit with wires, horn ELECTRIC HORN





With handlebar mounting bracket or Headlamp fitting for RMII 42/-d. SPEEDOMETER

LOW KOUR RALEICH MOPED DE LUXE ACCESSORIES



# RM6 RUNABOUT

#### £54.19.6 including Purchase Tax

The largest selling moped in the U.K. Designed to provide budget price motoring with utter reliability. Completely automatic transmission with only one engine control. The plus-power engine fitted to the 1966 model gives even better hill climbing and effortless cruising.

SPECIFICATION

Engine: 49.9 c.c. two-stroke, Aluminium cylinder with hard chromium plated bore. 1.7 B.H.P. at 5.000 r.p.m. Enrichment valve for cold starting. Sediment trap incorporated in carburettor. Transmission: Single-speed, with 'engine speed' double-action automatic clutch. Lighting: Direct lighting from flywheel alternator. 3' diameter headlamp. Rear lamp incorporating reflector. Frame: Pressed steel 'beam' pattern. Wheels: 23' x 2.0' tyres, chrome plated rims, rust proof spokes. Full width light alloy rear hub. Fuel Tank Capacity: 1.3/8 gallons. Equipment: Toolbag, Toolkit, centre stand, Number plates. Mattress saddle. Finish: Neptune Blue enamel with bright chrome plated fittings. Performance: Cruising speed 30 m.p.h. Fuel consumption up to 160 m.p.g.

# £97.19.6 including Purchase Tax

The last word in mopeds. A REAL two seater with every refinement. High power engine, auto gear change, front and rear suspension, dual seat and footrests, legshields, enclosed drive chain, quickly detachable rear hub—indeed the features could fill a book. Only owning one of these unbelievable Supermatics can give a true appreciation of the thought that goes into them. The only moped approved and chosen by Police Forces, H.M. Government, National Boards, as giving day in-day out reliability, supreme comfort, performance and economy. Just check the features of the Supermatic and you will know why this machine is the ultimate choice.

#### RM5 SUPERMATIC

#### SPECIFICATION

Engine: 49.9 c.c. two stroke. Aluminium cylinder with hard chromium plated bore. 2.66 B.H.P. at 5,600 r.p.m. Enrichment valve for cold starting. Sediment trap incorporated in carburettor. Transmission: Infinitely variable automatic gear change mechanism. 'Engine speed' double action automatic clutch. Lighting: Direct lighting from flywheel alternator. Console type headlamp with dipping device. Rear lamp incorporates reflector. Combined lighting switch and horn button on handlebar. Frame: Pressed steel 'beam' pattern incorporating petrol tank and tool compartment. Valanced Telescopic Forks. Swinging arm rear suspension. Wheels: 22.5" x 2.25" White wall tyres, chrome plated rims, rust proof spokes. 4" diameter full width alloy front hub. 4" diameter full width quickly detachable rear hub. Fuel Tank Capacity: 11 gallons with dip measure. Equipment: Dual seat, Pillion footrests, Pressed steel legshields with mudflaps. Chrome fuel tank covers, Chain case, Speedometer, Electric horn, polished alloy tool compartment covers, Toolkit, Inflator, Centre stand, Number plates. Finish: Dual tone Pearl Grey and Fire Red enamel or Dual tone Pearl Grey and Neptune Blue enamel with bright chrome plated fittings.




## RM6 RUNABOUT SUPER DE LUXE


#### £59.19.6 including Purchase Tax

A comprehensively equipped and finished version of the ever popular Runabout. Elegantly styled legshields, electric horn and light alloy inflator, coupled with the splendid flamboyant Royal Carmine finish, are built-in features adding up to unbeatable value.

Engine: 49.9 c.c. two-stroke. Aluminium cylinder with hard chromium plated bore. 1.7 B.H.P. at 5,000 r.p.m. Enrichment valve for cold starting, Sediment trap incorporated in carburettor. Transmission: Single-speed, with "engine speed" double-action automatic clutch. Lighting: Direct lighting from flywheel alternator. 3" diameter headlamp. Rear lamp incorporating reflector. Frame: Pressed steel beam pattern. Wheels: 23" x 2.0" tyres, chrome plated rims, rust proof spokes. Full width light alloy rear hub. Fuel Tank Capacity: 1.3/8 gallons including reserve. Equipment: Matching pressed steel legshields, Electric horn, Alloy tyre inflator, Toolbag, Toolkit, Centre stand, Number plates, Mattress saddle. Finish: Flamboyant Royal Carmine with bright chrome plated fittings. Performance: Cruising speed 30 m.p.h. Fuel consumption up to 160 m.p.g.

Each Raleigh Model described in this Catalogue has its own distinguishing features, but every one is powered by a precision die-cast light alloy, twostroke motor. These power units have been designed to eliminate the complications that identify cast iron barrelled four-stroke motors frequently fitted to current day lightweights and their need for 300 mile oil changes. Raleigh lubrication is metered according to engine speed so that maintenance is reduced to a minimum.






# **RM12 'SUPER 50'**

# £87.19.6 including Purchase Tax

Styled for the younger rider, the 'Super 50' has the mechanical specification of the RM.II but incorporates a long saddle so the rider can lay prone to reduce wind resistance. Sports style handlebars and flyscreen are fitted to give the 'Super 50' its magnificent extrovert appearance.

# SPECIFICATION

Engine: 49.9 c.c. two-stroke. Aluminium cylinder with hard chromium plated bore. 2.66 B.H.P. at 5,600 r.p.m. Enrichment valve for cold starting. Sediment trap incorporated in carburettor. Transmission: Infinitely variable automatic gear change mechanism. 'Engine speed' double action automatic clutch. Lighting: Direct lighting from flywheel alternator. 4' diameter headlamp. Rear lamp incorporating reflector. Frame: Pressed steel 'beam' pattern with valanced telescopic forks. Wheels: 23' x 2' yres, chrome plated rims, rust proof spokes. Full width light alloy hubs. Fuel Tank Capacity: 1½ gallons incorporating reserve. Equipment: Speedometer, Flyscreen, Electric horn, Twin chrome toolboxes, Toolkit, Inflator, Centre stand, Number plates, long racing pattern saddle. Finish: Pearl Grey enamel with red trim and bright chrome plated fittings. Performance: Top speed (rider upright) 45 m.p.h. Top speed (rider prone) 50 m.p.h. Fuel consumption 120 m.p.g.



# RM 11 'SUPER TOURIST'

# £79.19.6 including Purchase Tax


A brilliant new model designed for the longer journey—the front mounted tank enables the rider who prefers higher speeds—to 'steer with his knees'. A special high performance engine with automatic gear change and clutch, a magnificently sprung and padded saddle, extra wide touring handlebars, a sturdy chrome rear carrier part just a few of the features which make the are just a few of the features which make the 'Super Tourist' the finest touring moped ever

# SPECIFICATION

SPECIFICATION

Engine: 49.9 c.c. two-stroke, Aluminium cylinder with hard chromium plated bore. 2.66 B.H.P. at 5.600 r.p.m. Enrichment valve for cold starting. Sediment trap incorporated in carburettor. Transmission: Infinitely variable automatic gear change mechanism. 'Engine speed' double action automatic clutch. Lighting: Direct lighting from flywheel alternator. 4' diameter headlamp. Rear lamp incorporating reflector. Frame: Pressed steel 'beam' pattern with valanced telescopic forks. Wheels: 23' x 2' tyres, chrome plated rims, rust proof spokes. Full width alloy hubs. Fuel Tank Capacity: 1½ gallons incorporating reserve. Equipment: Electric horn, Twin chrome toolboxes, Toolkit, chrome Luggage carrier, Inflator, Centre stand, Number plates, Denfeld sprung seat with foam underlay. Finish: Flamboyant Royal Carmine with bright chrome plated fittings. Performance: Top speed 45 m.p.h. Fuel consumption 120 m.p.g.

# IceniCAM Information Service



www.icenicam.org.uk